


CM Cyclone hand chain hoist

One of the most popular and reliable hoists ever designed, the CM Cyclone combines superior engineering, efficiency and durability. Available in a variety of capacities from 1/4 ton to 10 tons, CM Cyclone features:

- Most interchangeability of parts in the industry
- Standard Load Limiter for simple, automatic overload protection
- Enclosed contoured Weston-type automatic brake for positive load control
- High-efficiency spur gearing for greater lift with minimum effort
- Rugged CM Hoistaloy chain for added strength and durability
- Fully machined, forged liftwheel pockets for easier lifting and smooth free chaining
- High-strength aluminum alloy castings in frame and covers
- Inspected over 75 times to meet or exceed HMI and ASME/ANSI performance and safety standards
- Standard hand chain drop is 2 feet less than lift, (example: 8 foot lift hoist has 6 foot hand chain drop)
- Chain containers, zinc-plated load and hand chain, aluminum unwelded hand chain, Latchlok hooks, bronze hooks, eye-type suspension, bullard hooks and units without Load Limiter optional, depending on capacity
- Lifetime warranty
- Made in U.S.A.



**1/4 to 2 ton
capacity**



**3 and 4 ton
capacity**



**5 and 6 ton
capacity**



**8 ton
capacity**



**10 ton
capacity**

Specifications

| Rated capacity* (tons) | Product code | Standard lift† (ft.) | Reeving | Minimum distance between hooks (in.) | Chain overhauled to lift load one foot (ft.) | Chain pull to lift full load (lbs.) | Shipping weight (lbs.) |
|---------------------------|--------------|-------------------------|---------|--------------------------------------|--|-------------------------------------|------------------------|
| 1/4 | 4621 | 8 | 1 | 12 7/8 | 22 1/2 | 23 | 37 |
| 1/2 | 4622 | 8 | 1 | 12 7/8 | 22 1/2 | 46 | 37 |
| 1 | 4624 | 8 | 1 | 14 | 30 | 69 | 40 |
| 1 1/2 | 4625 | 8 | 1 | 17 5/16 | 40 1/2 | 80 | 65 |
| 2 | 4626 | 8 | 1 | 17 5/16 | 52 | 83 | 64 |
| 3 | 4627 | 8 | 2 | 21 1/2 | 81 | 85 | 96 |
| 4 | 4628 | 8 | 3 | 21 1/2 | 104 | 88 | 96 |
| 5 | 4629 | 8 | 3 | 24 1/4 | 156 | 75 | 128 |
| 6 | 4630 | 8 | 3 | 25 1/4 | 156 | 90 | 132 |
| 8 | 4631 | 8 | 4 | 34 1/2 | 208 | 89 | 235 |
| 10 | 4632 | 8 | 5 | 35 1/2 | 260 | 95 | 249 |

† Can be supplied with longer lifts